Note: This datasheet may be out of date

Please download the latest datasheet of BLM15HB121SN1# from the official website of Murata Manufacturing

https://www.murata.com/en-eu/products/productdetail?partno=BLM15HB121SN1%23

### BLM15HB121SN1#

"#" indicates a package specification code.





REACH

< List of part numbers with package codes >

BLM15HB121SN1B BLM15HB121SN1D BLM15HB121SN1J



### Appearance & Shape













- 1. Small size: 1.0x0.5mm
- 2. Suitable for noise suppression in 1GHz or higher frequency
- 3. No Lead production using Ni+Sn plating in termination

#### **Applications**

- 1. EMI suppression for Note PC and DSC
- 2. Noise suppression for data line in mobile phone
- 3. Noise suppression for USB interface line in mobile phone
- 4. Prevention of erroneous operation caused by local oscillation signal in mobile phone



Other Usage
-------------

For general



### **Packaging Information**

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	10000
J	330mm Paper Tape	50000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/08/23



# BLM15HB121SN1#

Note: This datasheet may be out of date

"#" indicates a package specification code.

# Specifications

Shape	SMD
Size Code (in mm)	1005
Size Code (in inch)	0402
Length	1.0mm
Length Tolerance	±0.05mm
Width	0.5mm
Width Tolerance	±0.05mm
Thickness	0.5mm
Thickness Tolerance	±0.05mm
Impedance (at 100MHz)	120Ω
Impedance (at 100MHz) Tolerance	±25%
Impedance (at 1GHz)	500Ω
Impedance (at 1GHz) Tolerance	±40%
Rated Current (at 85°C)	300mA
Rated Current (at 125°C)	300mA
DC Resistance(max.)	0.7Ω
Operating Temperature Range	-55℃ to 125℃

Mass(typ.)	0.001g
Number of Circuit	1

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM15HB121SN1\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 

Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM15HB121SN1%23

2 of 3

### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/08/23


<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM15HB121SN1%23

# BLM15HB121SN1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

**Equivalent Circuit** 

3 of 3

#### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.