

< Silicon RF Power MOS FET (Discrete) >

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W

## DESCRIPTION

RD07MVS1 is a MOS FET type transistor specifically designed for VHF/UHF RF power amplifiers applications.

## FEATURES

High power gain:

$P_{out} > 7W$ ,  $G_p > 10dB$  @  $V_{dd} = 7.2V$ ,  $f = 520MHz$


High Efficiency: 60% typ. (175MHz)

High Efficiency: 55% typ. (520MHz)

## APPLICATION

For output stage of high power amplifiers in VHF/UHF band mobile radio sets.

## OUTLINE DRAWING



Terminal No.  
 ① Drain(output)  
 ② Source(GND)  
 ③ Gate(input)

Note  
 ( ): center value

## RoHS COMPLIANT

RD07MVS1 is EU RoHS compliant product.

RoHS compliant product is indicating by the letter "ZG" after the Lot Marking.

## ABSOLUTE MAXIMUM RATINGS

( $T_c = 25^\circ C$  UNLESS OTHERWISE NOTED)

SYMBOL	PARAMETER	CONDITIONS	RATINGS	UNIT
VDSS	Drain to source voltage	$V_{gs} = 0V$	30	V
VGSS	Gate to source voltage	$V_{ds} = 0V$	+/- 20	V
Pch	Channel dissipation	$T_c = 25^\circ C$	50	W
Pin	Input Power	$Z_g = Z_l = 50\Omega$	1.5	W
ID	Drain Current	-	3	A
Tch	Junction Temperature	-	150	$^\circ C$
Tstg	Storage temperature	-	-40 to +125	$^\circ C$
Rth j-c	Thermal resistance	Junction to case	2.5	$^\circ C/W$

Note: Above parameters are guaranteed independently.

**RD07MVS1**

RoHS Compliant, Silicon MOSFET Power Transistor,175MHz,520MHz,7W

**ELECTRICAL CHARACTERISTICS** (T<sub>c</sub>=25°C, UNLESS OTHERWISE NOTED)







SYMBOL	PARAMETER	CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX.	
I <sub>DSS</sub>	Zero gate voltage drain current	V <sub>DS</sub> =17V, V <sub>GS</sub> =0V	-	-	200	uA
I <sub>GSS</sub>	Gate to source leak current	V <sub>GS</sub> =10V, V <sub>DS</sub> =0V	-	-	1	uA
V <sub>TH</sub>	Gate threshold Voltage	V <sub>DS</sub> =12V, I <sub>DS</sub> =1mA	1.4	1.7	2.4	V
P <sub>out1</sub>	Output power	f=175MHz, V <sub>DD</sub> =7.2V	7	8	-	W
η <sub>D1</sub>	Drain efficiency	P <sub>in</sub> =0.3W, I <sub>dq</sub> =700mA	55	60	-	%
P <sub>out2</sub>	Output power	f=520MHz, V <sub>DD</sub> =7.2V	7	8	-	W
η <sub>D2</sub>	Drain efficiency	P <sub>in</sub> =0.7W, I <sub>dq</sub> =750mA	50	55	-	%
	Load VSWR tolerance	V <sub>DD</sub> =9.2V, P <sub>o</sub> =7W(Pin Control) f=175MHz, I <sub>dq</sub> =700mA, Z <sub>g</sub> =50Ω Load VSWR=20:1(All Phase)	No destroy			-
	Load VSWR tolerance	V <sub>DD</sub> =9.2V, P <sub>o</sub> =7W(Pin Control) f=520MHz, I <sub>dq</sub> =750mA, Z <sub>g</sub> =50Ω Load VSWR=20:1(All Phase)	No destroy			-

Note: Above parameters, ratings, limits and conditions are subject to change.

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W

## TYPICAL CHARACTERISTICS




# RD07MVS1


RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W

## TYPICAL CHARACTERISTICS


Pin-Po CHARACTERISTICS @f=175MHz




Pin-Po CHARACTERISTICS @f=175MHz




Pin-Po CHARACTERISTICS @f=520MHz




Pin-Po CHARACTERISTICS @f=520MHz



Vdd-Po CHARACTERISTICS @f=175MHz




Vdd-Po CHARACTERISTICS @f=520MHz



# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W


## TYPICAL CHARACTERISTICS



# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W


## TEST CIRCUIT(f=175MHz)



L: Enameled wire 7 Turns, D: 0.43mm, 2.46mm O.D.  
C1, C2: 1000pF, 0.0022μF in parallel

Note: Board material PTFE substrate  
Micro strip line width=2.2mm/50Ω, er:2.7, t=0.8mm  
W: line width=1.0mm

## TEST CIRCUIT(f=520MHz)



L: Enameled wire 5 Turns, D: 0.43mm, 2.46mm O.D.  
C1, C2: 1000pF, 0.0022μF in parallel


Note: Board material PTFE substrate  
Micro strip line width=2.2mm/50Ω, er:2.7, t=0.8mm  
W: line width=1.0mm

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor, 175MHz, 520MHz, 7W

## INPUT/OUTPUT IMPEDANCE VS. FREQUENCY CHARACTERISTICS

175MHz  $Z_{in}^*$   $Z_{out}^*$   
 $Z_o=10\Omega$




$V_{dd}=7.2V$ ,  $I_{dq}=700mA$ ( $V_{gg}$  adj.),  $P_{in}=0.28W$

$Z_{in}^*=1.55+j5.53$   
 $Z_{out}^*=3.24-j0.26$

$Z_{in}^*$ : Complex conjugate of input impedance  
 $Z_{out}^*$ : Complex conjugate of output impedance

520MHz  $Z_{in}^*$   $Z_{out}^*$   
 $Z_o=10\Omega$



$V_{dd}=7.2V$ ,  $I_{dq}=750mA$ ( $V_{gg}$  adj.),  $P_{in}=0.7W$

$Z_{in}^*=0.76+j0.06$   
 $Z_{out}^*=1.61-j0.52$

$Z_{in}^*$ : Complex conjugate of input impedance  
 $Z_{out}^*$ : Complex conjugate of input impedance

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor,175MHz,520MHz,7W

RD07MVS1 S-PARAMETER DATA (@Vdd=7.2V, Id=750mA)

Freq. [MHz]	S11		S21		S12		S22	
	(mag)	(ang)	(mag)	(ang)	(mag)	(ang)	(mag)	(ang)
100	0.890	-174.1	5.508	82.1	0.016	-3.6	0.790	-172.8
150	0.897	-175.6	3.613	75.0	0.015	-8.5	0.801	-174.0
175	0.899	-176.0	3.028	72.4	0.015	-9.6	0.802	-174.1
200	0.901	-176.3	2.604	70.1	0.014	-10.9	0.815	-174.0
250	0.907	-176.7	2.019	65.6	0.014	-12.7	0.844	-174.1
300	0.913	-177.0	1.614	60.7	0.012	-15.3	0.843	-174.1
350	0.918	-177.3	1.308	57.1	0.011	-15.8	0.860	-174.4
400	0.924	-177.8	1.102	54.1	0.010	-14.2	0.879	-175.0
450	0.928	-178.0	0.929	50.1	0.009	-14.8	0.882	-175.1
500	0.933	-178.3	0.790	48.6	0.008	-9.6	0.895	-175.5
520	0.935	-178.5	0.753	47.6	0.007	-7.7	0.901	-175.8
550	0.937	-178.8	0.692	45.3	0.007	-5.6	0.906	-176.2
600	0.940	-179.2	0.595	43.6	0.006	0.4	0.907	-176.6
650	0.942	-179.4	0.529	42.4	0.006	17.1	0.916	-177.2
700	0.944	-179.8	0.467	40.2	0.005	21.8	0.923	-177.6
750	0.947	-179.8	0.416	39.4	0.005	40.9	0.921	-178.0
800	0.948	-179.4	0.374	38.6	0.004	52.0	0.930	-178.8
850	0.949	-179.0	0.343	37.6	0.005	67.1	0.933	-178.9
900	0.951	-178.6	0.304	36.5	0.005	72.6	0.932	-179.3
950	0.951	-178.2	0.284	37.6	0.006	85.8	0.937	-179.8
1000	0.952	-177.9	0.262	35.1	0.007	85.1	0.938	-179.7
1050	0.950	-177.4	0.234	36.0	0.008	89.8	0.938	-179.3
1100	0.952	-176.9	0.226	35.8	0.009	93.4	0.940	-178.2

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor,175MHz,520MHz,7W

---

## ATTENTION:

- 1.High Temperature ; This product might have a heat generation while operation,Please take notice that have a possibility to receive a burn to touch the operating product directly or touch the product until cold after switch off. At the near the product,do not place the combustible material that have possibilities to arise the fire.
- 2.Generation of High Frequency Power ; This product generate a high frequency power. Please take notice that do not leakage the unnecessary electric wave and use this products without cause damage for human and property per normal operation.
- 3.Before use; Before use the product,Please design the equipment in consideration of the risk for human and electric wave obstacle for equipment.

## PRECAUTIONS FOR THE USE OF MITSUBISHI SILICON RF POWER DEVICES:

1. The specifications of mention are not guarantee values in this data sheet. Please confirm additional details regarding operation of these products from the formal specification sheet. For copies of the formal specification sheets, please contact one of our sales offices.
- 2.RA series products (RF power amplifier modules) and RD series products (RF power transistors) are designed for consumer mobile communication terminals and were not specifically designed for use in other applications. In particular, while these products are highly reliable for their designed purpose, they are not manufactured under a quality assurance testing protocol that is sufficient to guarantee the level of reliability typically deemed necessary for critical communications elements and In the application, which is base station applications and fixed station applications that operate with long term continuous transmission and a higher on-off frequency during transmitting, please consider the derating, the redundancy system, appropriate setting of the maintain period and others as needed. For the reliability report which is described about predicted operating life time of Mitsubishi Silicon RF Products , please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor.
3. RD series products use MOSFET semiconductor technology. They are sensitive to ESD voltage therefore appropriate ESD precautions are required.
4. In the case of use in below than recommended frequency, there is possibility to occur that the device is deteriorated or destroyed due to the RF-swing exceed the breakdown voltage.
5. In order to maximize reliability of the equipment, it is better to keep the devices temperature low. It is recommended to utilize a sufficient sized heat-sink in conjunction with other cooling methods as needed (fan, etc.) to keep the channel temperature for RD series products lower than 120deg/C(in case of Tchmax=150deg/C) ,140deg/C(in case of Tchmax=175deg/C) under standard conditions.
6. Do not use the device at the exceeded the maximum rating condition. In case of plastic molded devices, the exceeded maximum rating condition may cause blowout, smoldering or catch fire of the molding resin due to extreme short current flow between the drain and the source of the device. These results causes in fire or injury.
7. For specific precautions regarding assembly of these products into the equipment, please refer to the supplementary items in the specification sheet.
8. Warranty for the product is void if the products protective cap (lid) is removed or if the product is modified in any way from it's original form.
9. For additional "Safety first" in your circuit design and notes regarding the materials, please refer the last page of this data sheet.
10. Please refer to the additional precautions in the formal specification sheet.

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor,175MHz,520MHz,7W

## Main Revision for this Edition

No	Date	Revision	
		Pages	Points
1	2011.10.11	1-11 6 9	<ul style="list-style-type: none"><li>• Revision by change of style of data sheet.</li><li>• TEST CIRCUIT(f=175MHz)、(f = 520MHz) Note: The contents are changed. Note:Board material-Teflon substrate→Note:Board material-PTFE substrate</li><li>• PRECAUTION FOR THE USE OF MITSUBISHI SILICON RF POWER AMPLIFIER DEVICES: 2 .  The content of the above-mentioned item is changed.  Before it corrects it  2.RA series products (RF power amplifier modules) are designed for consumer mobile communication terminals and were not specifically designed for use in other applications. In particular, while these products are highly reliable for their designed purpose, they are not manufactured under a quality assurance testing protocol that is sufficient to guarantee the level of reliability typically deemed necessary for critical communications elements. Examples of critical communications elements would include transmitters for base station applications and fixed station applications that operate with long term continuous transmission and a higher on-off frequency during transmitting, especially for systems that may have a high impact to society.</li></ul>
2	2014.9.3	3-4	<p>Changed of the material that the Silver resin paste from the PbSnAg solder paste for the purpose of RoHS compliance.</p> <p>The reason of change is due to these applications, high-melting solder alloys are used,which is exception item at RoHS,and do not satisfy the requirements of RoHS. Also, Changed of the production site to THAILAND(MMT of EMS company ) from JAPAN,change to the EMS company standard material for Leadframe material,SLP package size is thinned to a thickened of EMS company standard size ( 0.9mm to0.75mm),and back side metal of MOSFET wafer from adequate for PbSnAg solder:</p> <p>Replaced of graphs.</p>

# RD07MVS1

RoHS Compliant, Silicon MOSFET Power Transistor,175MHz,520MHz,7W

## **Keep safety first in your circuit designs!**

Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

## **Notes regarding these materials**

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for the latest product information before purchasing a product listed herein.  
The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.  
Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Semiconductor home page (<http://www.MitsubishiElectric.com/>).
- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.  
Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for further details on these materials or the products contained therein.