

USP-120MFN-24DN- 462215



Switching power supply, output voltage DC: 24V, output voltage accuracy: $\pm 1\%$, rated output current: 5A, output current range: 0~5A, output power: 120W, width 32mm, height 125mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	41

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	24V
Output voltage accuracy	$\pm 1\%$
Rated output current(A)	5A
Output current range	0~5A
Output power	120W
Ripple and noise	120mVp-p
Setting range of voltage,DC	24-28V
Hold up time	8ms/115VAC , 16ms/230VAC
Efficiency	88%
Shock current	Cold start current 30A/115VAC , 55A/230VAC

Parameter	Data
Working temperature	-20 ~ +60
Ambient temperature (storage/transportation) ()	-40 ~ +85
Insulation impedance	100M Ω Ohms/500VDC/25 /70%RH
Safety standards	I/P-O/P:4KVAC
EMC standards	IS13252(Part1) &EN62368-1,IEC/UL/BS EN62368-1, UL61010-1,UL508

Dimension

Parameter	Data
Width(mm)	100
Thickness(mm)	36
Height(mm)	125