

USP-240MFA -24DN- 462217



Switching power supply, DC output voltage: 24V, output voltage accuracy: $\pm 1\%$, rated output current: 10A, output current range: 0-10A, output power: 240W, width 54mm, height 124mm

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	600

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	12V
Output voltage accuracy	$\pm 2\%$
Rated output current(A)	10A
Output current range	0~10A
Output power	240W
Ripple and noise	150mVp-p
Setting range of voltage,DC	24-28V
Hold up time	20ms/230VAC

Parameter	Data
Efficiency	94%
Shock current	Cold start current15A/115VAC , 30A/230VAC
Working temperature	-40 ~ +70
Ambient temperature (storage/transportation) ()	-40 ~ +85
Insulation impedance	100M Ω Ohms/500VDC/25 /70%RH
Voltage resistance	I/P-O/P:3KVAC
EMC standards	IS13252(Part1) &EN62368-1,IEC/UL/BS EN62368-1, UL61010-1,UL508

Dimension

Parameter	Data
Width(mm)	110
Thickness(mm)	54
Height(mm)	124