

USP-240MFA -12DXN- 462236



Switching power supply, output voltage DC: 12V, output voltage accuracy: $\pm 2\%$, rated output current :16A, output current range: 0~16A, output power: 192W, width41mm, height124mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	650

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	12V
Output voltage accuracy	$\pm 2\%$
Rated output current(A)	16A
Output current range	0~16A
Output power	192W
Ripple and noise	100mVp-p
Setting range of voltage,DC	12-14V
Hold up time	20ms/230VAC(full load)
Efficiency	92%
Shock current	Cold start current15A/115VAC , 30A/230VAC
Working temperature	-40 ~ +70
Ambient temperature	-40 ~ +85

Parameter	Data
(storage/transportation) ()	
Insulation impedance	50M Ω Ohms/500VDC/25 /70%RH
Safety standards	I/P-O/P:3KVAC
EMC standards	IS13252(Part1) &EN62368-1,IEC/UL/BS EN62368-1, UL61010-1,UL61010-2-201

Dimension

Parameter	Data
Width(mm)	110
Thickness(mm)	41
Height(mm)	124