

USP-480MFA-48DN- 462220



Switching power supply, output voltage DC: 48V, output voltage accuracy: $\pm 1\%$, rated output current: 10A, output current range: 0~10A, output power: 480W, width 48mm, height 125mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	980

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	48V
Output voltage accuracy	$\pm 1\%$
Rated output current(A)	10A
Output current range	0~10A
Output power	480W
Ripple and noise	70mVp-p
Setting range of voltage,DC	48-55V
Hold up time	22ms/230VAC
Efficiency	94.5%
Shock current	Cold start current 15A/115VAC , 15A/230VAC
Working temperature	-40 ~ +70

Parameter	Data
Ambient temperature (storage/transportation) ()	-40 ~ +85
Insulation impedance	100M Ω Ohms/500VDC/25 /70%RH
Voltage resistance	I/P-O/P:3KVAC
EMC standards	IS13252(Part1) &EN62368-1,IEC/UL62368-1, UL61010-1

Dimension

Parameter	Data
Width(mm)	131.5
Thickness(mm)	48
Height(mm)	125