

USP-60PFN-12DN- 462210



Switching power supply, output voltage DC: 12v, output voltage accuracy: $\pm 2\%$, rated output current: 4.5A, output current range: 0~4.5A, output power: 54W, width52mm, height58mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	175

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	12V
Output voltage accuracy	$\pm 2\%$
Rated output current(A)	4.5A
Output current range	0~4.5A
Output power	54W
Ripple and noise	120mVp-p
Setting range of voltage,DC	10.8-13.8V
Hold up time	15ms/115VAC,80ms/230VAC
Efficiency	88%
Shock current	Cold start current30A/115VAC , 60A/230VAC
Working temperature	-40 ~ +70
Ambient temperature	-40 ~ +85

Parameter	Data
(storage/transportation) ()	
Insulation impedance	100M Ω Ohms/500VDC/25 /70%RH
Voltage resistance	I/P-O/P:4KVAC
EMC standards	IS13252(Part1)&EN62368-1,UL/IEC 62368-1

Dimension

Parameter	Data
Width(mm)	92.66
Thickness(mm)	52
Height(mm)	58