

PRODUCT SPECIFICATION

DATE: 04/22/14'


cosmo
ELECTRONICS CORPORATION

SOLID STATE RELAY :
KSD215AC3


NO. 58032215

REV.
5
SHEET 1 OF 2

1. OUTSIDE DIMENSION : UNIT (mm)



2. SCHEMATIC : TOP VIEW



PRODUCT SPECIFICATION

DATE: 04/22/14'

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY : KSD215AC3	NO. 58032215	REV. 5
SHEET 2 OF 2			

3. Absolute Maximum Ratings

(Ta=25°C)

Parameter		Symbol	Rating	Unit
Input	Input signal voltage	V _{IN}	5-12	VDC
	Drop-out voltage	V _{do}	1	VDC
Output	RMS on-state current	I _T	15	Arms
	Peak one cycle surge current	I _{surge}	150	A
	Repetitive peak-off state voltage	V _{DRM}	600	V
	Operating frequency	f	47~70	Hz
	Critical rate of rise of on-state current	di/dt	50	A/us
	Load supply voltage	V _{out}	250	Vrms AC
Isolation voltage input to output		V _{iso}	4000	Vrms
Operating temperature		T _{opr}	-30~100	°C
Storage temperature		T _{stg}	-30~125	°C
Soldering temperature 10 sec		T _{sol}	260	°C

4. Electrical Characteristics

(Ta=25°C)

Parameter		Symbol	Conditions	MIN	TYP	MAX	Unit
Input	Pick-up voltage	V _{pu}	I _t =1Arms			4	VDC
	Input current	I _{in}	V _{in} =5~12V	5		35	mA
Output	On-state voltage	V _T	I _T =1Arms			1.5	Vrms
	Operating current	I _{op}	V _{out} =240vrms	50			mArms
	Leakage current	I _{leak}	V _{out} =240vrms			7	mArms
	Critical rate of rise of off-state voltage	dv/dt		50	200		V/us
	Zero-cross voltage	V _{ox}			YES		
	Load Voltage Rating	V _{out}	I _T =50mArms MIN	50		280	VAC
Minimum trigger current		I _{FT}	V _{DRM} =600V			25	mA
Isolation resistance input to output		R _{ISO}	DC500V	10			GΩ
Turn-on time		T _{on}	60Hz AC			8.3	mS
Turn-off time		T _{off}	60Hz AC			8.3	mS
Thermal resistance (between junction and case)		R _{th} (j-c)l			1.3		°C/W