

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited.
未经允许禁止传输、复制、编辑该文档, 以及利用其内容进行交流

借通用件登记
Common Part

原图号
Old Draw. No.

底图总号
Assembly No.

REVISION RECORD				
REV	CN	DESCRIPTION	DRFT	DATE

General information:
1.Material: Aluminium die-cast
2.Colour: Grey
3.Surface: Powder-coated
4.Operating temperature: -40°C~+125°C
5.Degree of protection acc.to DIN EN60529 for coupled connector: IP65
6.Outgoing direction: Side outgoing line
7.Thread specifications: M/PG
8.Hoods&Housings seal: NBR
9.Undimensioned Tolerances:




Pitch Range in mm		Nominal Dimension Range in mm						
TO	Over	TO	Over	TO	Over	TO	Over	0.1/10
6	10	10	24	30	60	60	100	150
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

HOW TO ORDER:
S16B-BM-1L.M

Locking lever — 1L: 1 levers(plastic) 2B: 2 bolts
2L: 2 levers(plastic) 4B: 4 bolts
1L.M: 1 levers(Metal)
2L.M: 2 levers(Metal)

Housing type — SE: Side entry
SEH: Side entry-high construction
TE: Top entry
TEH: Top entry-high construction
BM: Bulkhead mounted
SM: Surface mounted
SMH: Surface mounted-high construction
CC: Cable to cable
CCH: Cable to cable high construction

Serieis — S3A: 3A Compact type S6B: 6B Standard type
S10A: 10A Compact type S10B: 10B Standard type
S16A: 16A Compact type S16B: 16B Standard type
S32A: 32A Compact type S24B: S24B Standard type
S32B: S32B Standard type
S48B: S48B Standard type



Order number	A
S16B-SE-4B-M25	M25×1.5
S16B-SE-4B-M32	M32×1.5
S16B-SE-4B-PG21	PG21

订货号 Order No.	S16B-SE-4B-XXX	名称 Name	S16B边出线四耳上壳	未注公差 Tolerance	表面 Surface
项目 Item	签字 Signature	日期 Date		Tolerances Table	VDI21
设计 Design	CHH	2024.07.17	图号 Drawing No.	/	版本号 Revision Number
审核 Check	CHH	2024.07.17	材料 Material	/	重量 Weight
工艺 Process	-	-	物料号 Item No.	/	比例 Scale
标准化 Unify	-	-	...	第1页/共1页 1 of 1	mm
批准 Approve	XJ	2024.07.17	/	SUPU 宁波诺普电子有限公司 NINGBO SUPU ELECTRONICS CO.,LTD.	