

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited.
未经允许禁止传输、复制、编辑该文档，以及利用其内容进行交流

REVISION RECORD				
REV	CN	DESCRIPTION	DRFT	DATE

General information:
1.Material: Aluminium die-cast
2.Colour: Grey
3.Surface: Powder-coated
4.Operating temperature: -40℃~+125℃
5.Degree of protection acc.to DIN EN60529 for coupled connector: IP65
6.Outgoing direction: Top entry
7.Thread specifications: M/PG
8.Hoods&Housings seal: NBR
9.Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm					
Over 6 To 10	Over 10 To 24	Over 30 To 60	Over 60 To 100	Over 100 To 150	Over 150 To 200	0.1/10	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±2°




HOW TO ORDER:

S24B-BM-1L.M

Locking lever — 1L: 1 levers(plastic) 2B: 2 bolts
2L: 2 levers(plastic) 4B: 4 bolts
1L.M: 1 levers(Metal)
2L.M: 2 levers(Metal)

Housing type — SE: Side entry
SEH: Side entry-high construction
TE: Top entry
TEH: Top entry-high construction
BM: Bulkhead mounted
SM: Suface mounted
SMH: Suface mounted-high construction
CC: Cable to cable
CCH: Cable to cable high construction

Sereies — S3A: 3A Compact type S6B: 6B Standard type
S10A: 10A Compact type S10B: 10B Standard type
S16A: 16A Compact type S16B: 16B Standard type
S32A: 32A Compact type S24B: S24B Standard type
S32B: S32B Standard type
S48B: S48B Standard type



Order number	A
S24B-TE-4B-M25	M25×1.5
S24B-TE-4B-M32	M32×1.5
S24B-TE-4B-PG21	PG21

订货号 Order No.	S24B-TE-4B-XXX		名称 Name	S24B顶出线四耳上壳		未注公差 Tolerance	表面 Surface	
项目 Item	签字 Signature	日期 Date				Tolerances Table		VDI21
设计 Design	CHH	2024.07.19	图号 Drawing No.	/		版本号 Revision Number	重量 Weight	比例 Scale
审核 Check	CHH	2024.07.19	材料 Material	/		M0	/	1:1
工艺 Process	-	-	物料号 Item No.	/		第1页/共1页 1 of 1		mm
标准化 Unify	-	-		...		SUPU 宁波诺普电子有限公司 NINGBO SUPU ELECTRONICS CO.,LTD.		
批准 Approve	XJ	2024.07.19		/				

借通用件登记
Common Part

原图号
Old Draw. No.

底图总号
Assembly No.