

USP-240MFA-24DXN - 462237



Switching power supply, output voltage DC: 24V, output voltage accuracy: $\pm 1\%$, rated output current: 10A, output current range: 0~10A, output power: 240W, width 41mm, height 124mm.

Product parameter

Parameter	Data
Packing unit(pcs)	/
NW per piece(g)	650

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Color	grey
Output voltage,DC(V)	24V
Output voltage accuracy	$\pm 1\%$
Rated output current(A)	10A
Output current range	0~10A
Output power	240W
Ripple and noise	120mVp-p
Setting range of voltage,DC	24-28V
Hold up time	20ms/230VAC(full load)
Efficiency	94%
Shock current	Cold start current 15A/115VAC , 30A/230VAC

Parameter	Data
Working temperature	-40 ~ +70
Ambient temperature (storage/transportation) ()	-40 ~ +85
Insulation impedance	50M Ω Ohms/500VDC/25 /70%RH
Safety standards	I/P-O/P:3KVAC
EMC standards	IS13252(Part1) &EN62368-1,IEC/UL/BS EN62368-1, UL61010-1,UL61010-2-201

Dimension

Parameter	Data
Width(mm)	110
Thickness(mm)	41
Height(mm)	124