


Push-in terminal block - UJ6-4 - 421457



Push-in terminal block , rated voltage:800V , Max. operating current:32A, connection method : spring connection , number of connections : 2 , crimping range : 0.2mm² -6mm² , AWG : 24-10 , thickness:6.2mm , height: 35.2mm , color : grey , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	45
NW per piece(g)	7.72
Layers	1
Number of connections	2
Rated cross section(mm ²)	4
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	800
Rated current(A)	32
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Spring connection
Stripping length(mm)	13
Solid conductors(mm ²)	0.2-6
Solid conductors AWG	24-10
Stranded conductors(mm ²)	0.2-4
Stranded conductors AWG	24-12
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%

Dimension

Parameter	Data
Width(mm)	55
Thickness(mm)	6.2
Height(mm)	35.2

Business data

Parameter	Data
End cover -UJ6-4G - 422107-Packing unit (PCS)	100
End cover -UJ6-4G - 422107-NW per piece(g)	1.98
End cover -UJ6-4G - 422107-Width(mm)	55.8
End cover- UJ6-4G - 422107-Thickness(mm)	2.2
End cover- UJ6-4G - 422107-Height(mm)	29