



Constant Current Driver

Model: LC40W250-400



Model	Output Current	Input Current	Input Power	Output Power Range	PF	Efficiency	Output Voltage	No load Voltage
LC40W250-400	250mA	0.24A	46.6W	12.5-40.0W	0.95	90%	50-160V	200V
	300mA	0.24A	47.2W	15.0-40.5W			50-135V	
	350mA	0.24A	46.9W	17.5-40.25W			50-115V	
	400mA	0.24A	46.6W	20.0-40.0W			50-100V	

*** Test result @230V, 50Hz, Full Load.**

1. Parameters

category	Item	Technical Norm
Features	Output Type	Constant Current
	IP Grade	IP20
	Insulation Class	Class I
Input	Rated Input Voltage	220-240VAC
	Range of Input Voltage	198-264VAC
	Frequency	50/60Hz
	Input Current	≤0.24A (230VAC, full load)
	Input Power	≤47.2W (230VAC, full load)
	Power Factor	≥0.95(230VAC, full load)
	THD	≤15% (230VAC, full load)
	No-load Power Consumption	≤0.5W @230VAC
	Inrush Current	≤40A/400us (230VAC, Full-load)
	Connected quantity of 16A Breaker	15pcs/type B ; 24pcs/type C @ 230Vac
	Input Over Voltage protection	When input voltage over 330-390VAC , output will be cut off, and can withstand 2 hrs. That is auto recovery, when input voltage come back normal input voltage range.
Output	Current Accuracy	±5%
	Max. Output Power	40.5W

	Max. Output Voltage(Uout) 最大输出电压	200V
	Started Delay Time 启动延时	≤0.5S (230VAC, full load)
	Current Ripple 纹波电流	±5% (Imax-Imin) / (Imax+Imin)
	PSTLM	≤1
	SVM	≤0.4
Protection 保护特性	Short Circuit Protection 短路保护	Auto Recovery
	Overload Protection 过载保护	Auto Recovery
	No-load Protection 空载保护	Auto Recovery
	Insulation voltage 绝缘电压	I/P to O/P , 3KVac/1min
	Insulation resistance 绝缘电阻	>100M ohm @ 500VDC
	Leakage current 漏电流	I/P to O/P < 700μA
Environment 使用环境	Ta/Operation Temperature 工作温度	-20...+50℃
	Ts/Storage Temperature 储存温度	-30...+85℃
	Tc/Enclosure Temperature 外壳温度	85℃
	Humidity 湿度	10%....90%RH
	Atmosphere 大气压强	86-108KPa
Construction 安装	Connection Method 连接方式	Push-in Terminal 推入式端子
	Installation 安装方式	Build-in 内置式
	PRI Wire preparation 输入线径	0.75-1.5☑
	SEC Wire preparation 输出线径	0.5-1.5☑
	Dimension 尺寸	230*30*21mm (L*W*H)
Standards 标准	Certification 证书	CE、EAC
	Safety Standards 安全标准	EN61347-1,EN61347-2-13
	EMC Standards 电磁兼容标准	EN55015,EN61000-3-2,EN61000-3-3,EN61547
	Performance 性能标准	EN62384
	Surge 浪涌	L-N:1KV; L/N-PE:2KV;
Others 其它	RoHS 环保	complied to 2011/65/EU
	Life Time 寿命	50000h Ta/Tc
Remark/备注 1.All Parameters, if not specified, are measured at 230VAC/50Hz and 25℃ ambient temperature. 2.LED Driver is a component of the luminaires, Luminaires and wire layout will affect the EMC, please check the EMC with end products again.		



6.Wiring instructions 接线说明

- All connections must be kept as short as possible to ensure good EMI behaviour

所有的连接线尽可能的短，以保证良好的 EMI

- Mains leads should be kept apart from LED Driver and other leads (ideally 5 – 10 cm distance)

电源线应和驱动器以及其他连接线保持一定的距离（建议 5-10cm）

- Advice the maximum length of output wires is 3 m

建议输出线的最大长度不超过 3m

- Secondary switching is not permitted (Except for constant voltage)

不允许二次侧开关（恒压除外）

- Incorrect wiring can damage LED modules.

错误的布线会损坏 LED 模组

- The wiring must be protected against short circuits to earth (sharp edged metals parts, metal cable clips, louver, etc.)

防止线路电线对地短路。（尖锐的金属零件、金属电缆夹、百叶窗等）

7. REVISION HISTORY 修订历史

[illegible]