



SPECIFICATION FOR PRODUCT

Part name: TERMINAL BLOCK

Part No.: JUT1-10PE

Customer P/N:

Date: 2021-12-14

Seller Confirmation

Written by	H.C
Checked by	Jammy.ling
Approved by	Eric

Customer Confirmation

Project Audit	
Structure Audit	
Security Certification	
Quality Approval	

Seller: Utility Electrical Co., Ltd

Add: huanghua,yueqing,wenzhou,zhejiang

Tel: 0577-62658888 Fax: 0577-62722319

E-Mail:jammy.ling@china-utl.com

Customer P/N:

Part No:JUT1-10PE

Revision for JUT1-10PE

Item No	Edition	Part Revised	Date Revised
1	A	put in file	2021-12-14
2			
3			
4			
5			
6			
7			
8			


1. TYPE: JUT1-10PE



Naming system:

Series JUT 1 - 10 PE **Ground Function**
Connecting Capacity

2.DRAWING&SIZES



OVERALL SIZES TOLERANCE

>120	±0.80
>30~120	±0.50
>6~30	±0.40
0~6	±0.25

3. BOM TABLE

ITEM.	PART NAME	MATERIAL	SURFACE OF CONTACT	QUANTIT Y (PCS)
(1)	HOUSING	PA66(UL94 V-0)		2
(2)	SCREW	BRASS	Ni Plated	2
(3)	BLOCK	BRASS	Ni Plated	2
(4)	TERMINAL	COPPER	Tin Plated	1
(5)	Grounding component	BRASS\STEEL	Ni Plated \Zn Plated	1

4. WIRE ENTRANCE: One input,one output

THICKNESS: 10.2mm

WIRE RANGE: 20-6AWG(0.5-16mm²) Sol

20-8AWG(0.5-10mm²) Str

5. TECHNICAL DATA:

MAX. TORQUE: 1.2 N*m

BREAKDOWN VOLTAGE: 8000V

INSULATION RESISTANCE: DC500V, More than500MΩ

STRIPPING LENGTH : 10.0 mm

6. WORKING CONDITION:

OPERATING TEMPERATURE: -40℃~+105℃

ALTITUDE: Less than 2000m 40Kpa~80KPa

RELATIVE HUMIDITY: 5%~95%

POLLUTION DEGREE: III

7. APPLICABLE STANDARDS

IEC 60998-1

IEC 60998-2-1

IEC 60947-1

IEC 60947-7-2

UL 1059

UL 486E

CSA22.2 158-1987

GB 14048.1

GB 14048.8

8. PROCEDURE

This type of terminal blocks fixed on Din rail , suitable to solid wire and strand wire connecting.



Solid wire



stranded wire

9. PACKAGE: Tightly Sealed