



SPECIFICATION FOR PRODUCT

Part name: TERMINAL BLOCK

Part No.: JUT1-4/2-2PE

Customer P/N:

Date: 2022-03-14

Seller Confirmation

Written by	H.C
Checked by	Jammy.ling
Approved by	Eric

Customer Confirmation

Project Audit	
Structure Audit	
Security Certification	
Quality Approval	

Seller: Utility Electrical Co., Ltd

Add: huanghua,yueqing,wenzhou,zhejiang

Tel: 0577-62658888 Fax: 0577-62722319

E-Mail:jammy.ling@china-utl.com

Customer:	Customer P/N:
Seller: ZheJiang Utility Electrical Co., Ltd	Part No:JUT1-4/2-2PE


Revision for JUT1-4/2-2PE

Item No	Edition	Part Revised	Date Revised
1	A	put in file	2022-03-14
2			
3			
4			
5			
6			
7			
8			


1. TYPE: JUT1-4/2-2PE



Naming system:



2.DRAWING&SIZES



OVERALL SIZES TOLERANCE

>120	±0.80
>30~120	±0.50
>6~30	±0.40
0~6	±0.25

3. BOM TABLE

ITEM.	PART NAME	MATERIAL	SURFACE OF CONTACT	QUANTIT Y (PCS)
(1)	HOUSING	PA66(UL94 V-0)		2
(2)	SCREW	BRASS	Ni Plated	2
(3)	BLOCK	BRASS	Ni Plated	2
(4)	Grounding component	BRASS\STEEL	Ni Plated \Zn Plated	1

4. WIRE ENTRANCE: Two input,two output

THICKNESS: 6.2mm

WIRE RANGE: 24-12AWG(0.2-4mm²) Sol

24-12AWG(0.2-4mm²) Str

5. TECHNICAL DATA:

MAX. TORQUE: 0.5 N*m

BREAKDOWN VOLTAGE: 4000V

INSULATION RESISTANCE: DC500V, More than500MΩ

STRIPPING LENGTH : 8 mm

6. WORKING CONDITION:

OPERATING TEMPERATURE: -40℃~+105℃

RELATIVE HUMIDITY: 5%~95%

POLLUTION DEGREE: III

7. APPLICABLE STANDARDS

IEC 60998-1

IEC 60998-2-1

IEC 60947-1

IEC 60947-7-2

UL 1059

UL 486E

CSA22.2 158-1987

GB 14048.1

GB 14048.8

8. PROCEDURE

This type of terminal blocks fixed on Din rail , suitable to solid wire and strand wire connecting.



Solid wire



stranded wire

9. PACKAGE: Tightly Sealed