



产 品 规 格 书


SPECIFICATION FOR APPROVAL

产 品 名 称 :	导轨式接线端子
Product name	Rail-type Terminal Blocks
产 品 型 号 : Part NO.	UPT-4RD/LED60
客户产品型号 : Customer part NO.	---
批 准 日 期 : Approval date	2023/1/5


I . 制造方审批/Manufacturer's Approval				
设计 designed by		审核 Audit by	批准 Approved by	
张群燕		youndy	杨勇	
II . 客户审批/Customer Approval				
质量工程师/Quality Engineer		审核/Audit by	批准/Approved by	
III. 修订履历/Revision Notes				
序号 No.	版本 Version	修订内容 Revise contents	修订者 Reviser	修订日期 Revision date
1	A	INITIAL RELEASE	张群燕	2023/1/5
2				
3				
4				
5				
6				

IV.产品简述及型号说明/Product description and Naming System:

1.产品简述/Product description




- 直插式连接技术,无需工具即可直接将刚性导线和带冷压头的导线连接至接线点。
Push-in connection technology was developed for direct conductor connection. Rigid conductors and conductors with ferrules can be directly contacted in the conductor connection point without using any tools.
- 插入力小，省心省力
Convenient plugging with lower insertion force
- 弹簧结构，导线拔出力大
High conductor pull-out forces due to the spring design
- 无需专用工具，即可轻松释放导线
The conductor can be easily released without special tools



2. 命名规则/Naming System:

UPT - 4 RD / LED60 - BK




- 外壳颜色：黑色
Housing color:Black
- 带60V DC的LED的悬臂式保险丝端子
Cantilever fuse terminal with 60V DC LED
- 保险丝功能
Fuse function
- 额定横截面
Nominal cross section
- 系列
Series

V. 技术参数/Technical Specification		
序号 No.	项目 Item	数据 Data
1	连接符合标准/Connection in acc. with standard	IEC 60947-7-3, IEC 60998, IEC 60947-1 , UL1059, GB 14048.1 , GB 14048.18
2	产品类型/Product type	保险丝接线端子/Fuse terminal block
3	应用领域/Area of application:	铁路工业/Railway industry
		机械工程/Machine building
		工厂工程/Plant engineering
		--
4	外形尺寸/Boundary dimension (L*W*H) 【mm】	55.8*6.2*63.34
5	接线方式/ Connection method	直插式连接/Plug-in connection
6	连接方向/Direction of Conductor connection	顶部连接/Top connection
7	连接量/connections	2
8	层数/Number of rows	1
9	每层连接数量/Number of connections	2
10	额定横截面/Nominal cross section 【mm ² 】	4
11	额定电压Nominal voltage IEC/UL 【V】	60/300
12	额定电流/Nominal current IEC/UL 【A】	6.3/6.3
	最大负载电流/Maximum load current 【A】	6.3
13	螺钉规格/Screw type	--
14	紧固扭矩/Torque 【Nm】	--
15	剥线长度/Stripping length 【mm】	10-12
16	接线范围/Connection range 【mm ² 】	--
	1) IEC: 刚性导线/Solid 【mm ² 】	0.2-6
	柔性导线/Flexible 【mm ² 】	0.2-6
	2) UL: 刚性导线/Solid 【AWG】	24-10
	柔性导线/Flexible 【AWG】	24-10
	3) 柔性导线横截面（套管，不带塑料绝缘管）/ Conductor cross section flexible, with ferrule without plastic sleeve 【mm ² 】	0.25-4
	4) 柔性导线横截面（带塑料绝缘管的套管）/ Conductor cross section flexible, with ferrule with plastic sleeve 【mm ² 】	0.25-4
	5) 2根具有相同横截面的导线，柔性，带TWIN套管及 塑料套管/2 Conductors with same cross section, flexible, with TWIN ferrule and plastic sleeve 【mm ² 】	0.5-1

	直接插拔式连接横截面/Connection cross sections directly pluggable:	--
17	1) 硬导线横截面/Conductor cross section solid	0.5-6
	2) 柔性导线横截面 (套管, 不带塑料绝缘管) / Conductor cross section flexible, with ferrule without plastic sleeve 【mm ² 】	0.5-4
	3) 柔性导线横截面 (带塑料绝缘管的套管) / Conductor cross section flexible, with ferrule with plastic sleeve 【mm ² 】	0.5-4
18	额定浪涌电压/Rated surge voltage 【KV】	6
19	工频耐压/Power frequency withstand voltage 【KV】	--
20	温升测试/ Temperature-rise test 【℃】	Increase in temperature ≤ 45
21	接触电阻测试/Contact resistance test 【m Ω】	≤ 20
22	导线拔出测试/Pull out force test of conductor	acc. IEC60947-1 : 2020 clause 9.2.5.4 and table 5
23	绝缘电阻测试/Insulation resistance test	≥500MΩ (DC500±50V, Hold for 1 minute)
24	导线机械插拔/Wire insertion and removal	The 6mm ² Solid wire can be removed by pressing the button
25	阻燃等级/Flammability rating according to UL 94	V0
	环境条件/Ambient conditions:	--
26	1) 环境温度 (运行) /Operating temperature 【℃】	-40℃~+105℃ (Depends on the derating curve)
	2) 环境温度 (存放/运输) / Ambient temperature (storage/transport) 【℃】	-25℃ - 60℃ (for a short time, not exceeding 24 h, -60℃ to +70℃)
	3) 允许湿度 (存放/运输) / Permissible humidity (storage/transport)	30 % ... 70 %
	4) 海拔/Altitude	Within 2000m, 40Kpa~80KPa
	5) 相对湿度/Relative humidity	5%~95%
27	安装类型/Mounting type:	NS 35/7,5 or NS 35/15
28	过电压类别&污染等级/ Overvoltage category & Degree of pollution:	III/3
	产品环保合规性/Environmental Product Compliance:	
29	● ROHS	No hazardous substances above threshold values
	● REACH SVHC	No hazardous substances above threshold values
30	质保期/Warranty:	12 Months
31	注意事项/Notice	电流取决于所用保险丝, 电压取决于指示灯 The current depends on the fuse used and the voltage depends on the indicator light.。


VI. 图纸/Drawing:

装配图
(Assembly drawing)



外形尺寸公差/External dimensional tolerance			
>0~6	>6~30	>30~120	>120
±0.25	±0.4	±0.5	±0.8

接插组件图
(Connector assembly drawing)



外形尺寸公差/External dimensional tolerance			
>0>6	>6~30	>30~120	>120
±0.25	±0.4	±0.5	±0.8

VII. BOM表/BOM TABLE:				
序号 No.	零件名称 part name	材 质 Material	表面处理 Surface treatment	数量 Quantity
装配（Assembly）BOM				
(1)	接插组件 connector assembly	/	/	1
(2)	外壳 Housing	PA66	N/A	1
(3)	按钮 button	PA66	N/A	2
(4)	弹簧 Spring	Stainless steel	N/A	2
(5)	短导电片 Short conductive sheet	Copper	Sn Plating	1
(6)	长导电片 Long conductive sheet	Copper	Sn Plating	1
接插组件（connector assembly）BOM				
(1)	接插主体Plastic part body of connector	PA66	N/A	1
(2)	灯珠 Lamp beads	Red	N/A	1
(3)	电阻 Resistance	AC-1/4W 15K	N/A	1
(4)	左导电片 Left conductive sheet	Copper	Sn Plating	1
(5)	右导电片 Right conductive sheet	Copper	Sn Plating	1
(6)	接插盖子 Connector plastic cover	PA66	N/A	1
(7)	接插固定盖子 Plastic fixed cover of connector	PA66	N/A	1

VIII. 产品认证/Product Certification



IX. 产品包装/Packaging



产品图片/Product picture



内盒/inner box



包装完成品/Packaged finished



外箱(封箱前)/Carton(Before sealing)

