



尺寸 Size:92mmx92mmx25mm
风量 Airflow:37~58m3/hr
22~34CFM

重量 Weight:268g
噪音 Noise:28~40dBA
风叶 Impeller: PBT Thermoplastic Black,UL94-V0
外框 Frame:Aluminum Alloy
端子 Terminals:0.5mm
引线 Lead Wire: AWG#22 UL 1007(Optional)
马达 Motor:Shaded Pole Induction Motor
安规认证 Safety:UL > CUL > TUV > CE >
温度范围 Operation Temperature:-10°C~+65°C

Model (型号)	Bearing System (轴承型式)	Voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G9225HA,S	Sleeve	100-125	50/60	0.14	13	2300/2800	34/40	47/58	28/34	1	/
G9225HA,S		200-240	50/60	0.07	13	2300/2800	34/40	47/58	28/34	1	/
G9225HA,B	Ball	100-125	50/60	0.14	13	2300/2800	34/40	47/58	28/34	1	/
G9225HA,B		200-240	50/60	0.17	13	2300/2800	34/40	47/58	28/34	1	/
G9225MA,S	Sleeve	100-125	50/60	0.14	13	1800/2300	28/35	37/45	22/26	1	/
G9225MA,S		200-240	50/60	0.07	13	1800/2300	28/35	34/45	22/26	1	/
G9225MA,B	Ball	100-125	50/60	0.14	13	1800/2300	28/35	37/45	22/26	1	/
G9225MA,B		200-240	50/60	0.07	13	1800/2300	28/35	37/45	22/26	1	/

